

CHERY MOTOR OIL

5W-40

Engine oil for CHERY
passenger cars

Specification

- API SP
- ACEA A3/B4

Product description

Premium engine oil based on synthetic technology. The product is specially intended for modern engines of CHERY passenger cars including engines fitted with turbo-charger.

Product description

Recommended for all-season use in gasoline engines (without particulate filters) for CHERY cars both during warranty and after-warranty periods.

Benefits

MAXIMUM PROTECTION

Suitable for extreme start-stop, idling and traffic jam conditions

ENGINE CLEANLINESS

Great dispersant and detergent properties prevent deposits formation on engine parts

EASY COLD START

Excellent low-temperature properties of synthetic base oils provide easy cold start

Property	Test methods	CHERY MOTOR OIL 5W-40
Kinematic viscosity at 100°C, mm ² /s	GOST 33 / ASTM D445	14,5
Viscosity index	GOST 25371 / ASTM D 2270	166
Dynamic viscosity (CCS) at -30°C, mPa·s	ASTM D5293 / GOST 52559	4 400
Dynamic viscosity (MRV) at -35°C, mPa·s	ASTM D4684 / GOST 52257	38 500
Total Base Number, mg KOH/g	GOST 30050 / ASTM D2896	10,0
Sulphated Ash, %mass	GOST 12417 / ASTM D874	1,1
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	9,8
Flash Point COC, °C	GOST 4333 / ASTM D92	234
Pour Point, °C	GOST 20287 (method B)	-42

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances.